"KNOCK-KNOCK"

Community Stakeholder Perspective on Vapor Intrusion

Lenny Siegel

Center for Public Environmental Oversight
Nation Forum on Vapor Intrusion
Philadelphia — January 12, 2009

"Who's there?"

"I'm here from the government (or a private polluter) to tell you that we need to drill holes in your floor because cancer-causing substances may be intruding into your home around the clock."

Key Issues

- Communications
- Property Value
- Sampling
- Mitigation
- Source Control
- Long-Term Management & Monitoring
- Land Use & New Construction
- Standards

Communications



Property Value












Mitigation



Mitigation




Mitigation



Source Control



Source Control



Source Control




Long-Term Management & Monitoring




Long-Term Management & Monitoring



Long-Term Management & Monitoring















Standards



Standards



Standards

Soil Vapor/Indoor Air Matrix 1

October 2006

SUB-SLAB VAPOR CONCENTRATION of COMPOUND (mcg/m³)	INDOOR AIR CONCENTRATION of COMPOUND (mcg/m ³)			
	< 0.25	0.25 to < 1	1 to < 5.0	5.0 and above
< 5	1. No further action	Take reasonable and practical actions to identify source(s) and reduce exposures	Take reasonable and practical actions to identify source(s) and reduce exposures	Take reasonable and practical actions to identify source(s) and reduce exposures
5 to < 50	5. No further action	6. MONITOR	7. MONITOR	8. MITIGATE
50 to < 250	9. MONITOR	10. MONITOR / MITIGATE	11. MITIGATE	12. MITIGATE
250 and above	13. MITIGATE	14. MITIGATE	15. MITIGATE	16. MITIGATE

No further action:

Given that the compound was not detected in the indoor air sample and that the concentration detected in the sub-slab vapor sample is not expected to significantly affect indoor air quality, no additional actions are needed to address human exposures.

Take reasonable and practical actions to identify source(s) and reduce exposures:

The concentration detected in the indoor air sample is likely due to indoor and/or outdoor sources rather than soil vapor intrusion given the concentration detected in the sub-slab vapor sample. Therefore, steps should be taken to identify potential source(s) and to reduce exposures accordingly (e.g., by keeping containers tightly capped or by storing volatile organic compound-containing products in places where people do not spend much time, such as a garage or outdoor shed). Resampling may be recommended to demonstrate the effectiveness of actions taken to reduce exposures.

MONITOR

Monitoring, including sub-slab vapor, basement air, lowest occupied living space air, and outdoor air sampling, is needed to determine whether concentrations in the indoor air or sub-slab vapor have changed. Monitoring may also be needed to determine whether existing building conditions (e.g., positive pressure heating, ventilation and air-conditioning systems) are maintaining the desired mitigation endpoint and to determine whether changes are needed. The type and frequency of monitoring is determined on a site-specific and building-specific basis, taking into account applicable environmental data and building operating conditions. Monitoring is an interim measure required to evaluate exposures related to soil vapor intrusion until contaminated environmental media are remediated.

MITIGATE

Mitigation is needed to minimize current or potential exposures associated with soil vapor intrusion. The most common mitigation methods are sealing preferential pathways in conjunction with installing a sub-slab depressurization system, and changing the pressurization of the building in conjunction with monitoring. The type, or combination of types, of mitigation is determined on a building-specific basis, taking into account building construction and operating conditions. Mitigation is considered a temporary measure implemented to address exposures related to soil vapor intrusion until contaminated environmental media are remediated.

MONITOR / MITIGATE:

Monitoring or mitigation may be recommended after considering the magnitude of sub-slab vapor and indoor air concentrations along with building- and site-specific conditions.

See additional notes on page 2.

MATRIX 1 Page 1 of 2

Guidance

- States
 - New York
 - California
 - New Jersey
 - ITRC
- Federal
 - EPA (2002 draft)
 - DOD hopefully out soon

Lessons

- Residents' cooperation is essential.
- Explain carefully and simply.
- People prefer direct air measurement.
- Residents like "blanket" mitigation.
- Source cleanup is the long-term solution.
- Monitor for the life of the contamination.
- Address VI before building.
- Protective standards are needed.
- Federal guidance is overdue.

E-mail me or give me your card if you want to join CPEO's free *Brownfields Internet Forum* and/or *Military Environmental Forum* newsgroup.

Lenny Siegel

Center for Public Environmental Oversight c/o PSC, 278-A Hope St., Mountain View, CA 94041

Voice: 650/961-8918 — Fax: 650/961-8918

Isiegel@cpeo.org — http://www.cpeo.org